HIGH PERFORMANCE MASKING FILM

AND I'M





HIGH PERFORMANCE MASKING FILM

Norton Plastifilm provides the perfect solution for excellent protection of car bodywork when spraying primer and paint during the repair process. Now available in 3 quality tiers, Standard, Premium & Ultra.



- EASY TO POSITION FOR FASTER CYCLE TIME
- SUITABLE FOR STANDARD PAINT BOOTH OVENS & INFRA-RED DRYING
- PREVENTS IMPRINT MARKING ON DAMP VEHICLES

NEW PLASTIFILM ULTRA



Plastifilm Ultra leaves no marks when used on damp cars, provides extra width and has a thicker film for better wear resistance and no tearing. Ultra resistance, absorption and protection.

FEATURES

- High density polyethylene+
- Anti-paint-flaking treatment
- Heat resistant up to 110°C
- Made of recyclable material

BENEFITS

- Anti-sweating, no marks if used on damp cars
- Water resistant, tough and tear resistant
- No bleed through of water based or solvent based products, excellent paint absorption
- Withstands spray booth temperatures

PLASTIFILM PREMIUM

Higher resistance to temperature and wear & tear.

FEATURES

- High density polyethylene
- Resistant temperatures up to 110°C and infra-red drying
- Static treatment
- 'Corona' treatment



BENEFITS

- Resistant to both water-based and solvent-based paint
- Reduce process & cycle time
- Within working range of all spray booths
- One product for all applications
- Excellent adhesion to the surface of the car
- Moulds to car shape immediately without tearing
- Work faster & more efficiently
- No dust contamination
- Prevents inprint marking on damp vehicles
- No humidity between film & coating

PLASTIFILM STANDARD

Good performance in all applications.

FEATURES

- Transparent polyethylene
- Closed surface structure
- Can be compressed to minimum dimensions
- Long length film also available



BENEFITS

- Excellent visibility
- Can be easily trimmed to size
- Prevents paint leaking through, avoiding rework
- Less waste & easy storage
- Lasts longer

NEW PLASTIFILM ULTRA

| TYPE | DIMENSIONS WxL | ART NO. | ΡΚ QTY |
|-------|-------------------|-------------|--------|
| Ultra | 4m x 150m | 63642504273 | 1 |
| | 5m x 120m | 63642504393 | 1 |
| | 6m x 100m | 63642504396 | 1 |



PLASTIFILM PREMIUM

| Plastifilm |
|------------|
| |

Plastifilm

| ТҮРЕ | DIMENSIONS WxL | ART NO. | ΡΚ QTY |
|---------|-------------------|-------------|--------|
| Premium | 4m x 150m | 66623341457 | 1 |
| | 5m x 120m | 66623341458 | 1 |

PLASTIFILM STANDARD



ACCESSORIES

| DESCRIPTION | ART NO. | ΡΚ QTY |
|--------------------------|-------------|--------|
| Dispenser for Plastifilm | 66623341459 | 1 |
| Cutter for Plastifilm | 07660708055 | 50 |





FITTING INSTRUCTIONS

Norton Plastfilm is clearly marked with the Norton logo as a positional guide to ensure the correct side of the film is placed on the car.



Correct



Incorrect



Corona treatment reduces the risk of imprinting on damp vehicles

www.norton.eu

Saint-Gobain Abrasives European Headquarters Rue de l'Ambassadeur - B.P.8 F78702 Conflans-Saint-Honorine France

Tel: +33 (0) 134 90 40 00 Fax: +33 (0) 139 19 89 56 Norton is a registered trademark of Saint-Gobain Abrasives. Form # 2757

SAINT-GOBAIN